

QuickLOAD® V.3.6 © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

WARNING: Since we have no control over equipment or data which may be used with this program, no responsibility is implied or assumed for results obtained through its use. Input data and results may be incorrect or wrong. Therefore the use of this data for loading ammunition can cause serious injury to personnel and material. The computer-results had to be checked against data available in current loading manuals.

LOT-TO-LOT VARIATIONS OF POWDERS, PRIMER SUBSTITUTION AND COMPONENT CHANGE OFTEN RAISE PRESSURES TO UNSAFE LEVELS. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS DATA FOR LOADING PURPOSES.

QuickLOAD® V.3.6.02 #130542, © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

User Data:	Date:8-Apr-2015	Time:22:27:00	File: xpert 25 wssm 80gr.dat	
Cartridge / Caliber	.25 WSSM	Bullet	.257, 80, XPERT	
Maximum Average Pressure, allowed	64542 psi.	4450 bar (Piezo CIP)	with flatbase	
Groove Caliber	0.257 in.	6.53 mm	Bullet Weight	80.0 gr. 5.18 gm
Case Capacity, overflow	54.31 gr. H2O	3.526 cm ³	Bullet Length	1.063 in. 27.0 mm
Case Length	1.660 in.	42.16 mm	Bullet Seating Depth	0.479 in. 12.17 mm
Cartridge O.A. Length	2.244 in.	57.0 mm	Barrel/Tube Length	24.0 in. 609.6 mm
Shot Start / Init Pressure	3625 psi.	249.94 bar	Cross Section Area of Bore	0.05118 in. ² 0.3302 cm ²
Propellant type	Somchem S335			
Charge Weight	39.0 gr.	2.527 gm	Load Density	204.8 gr./in. ³ 0.810 gm/cm ³
Heat of Explosion, Potential	240.4 J/gr.	3710 J/gm	Energy Density of Charge	49276 J/in. ³ 3007 J/cm ³
Propellant Solid Density	407.15 gr./in. ³	1.61 gm/cm ³	Used Ratio of Specific Heats cp/cv	1.224
Burning Rate Factor Ba	0.624 1/s		Weighting Factor	0.5
Burning Function Limit Z1	0.35		Prog.-/ Degressivity Factor a0	2.299
Factor b	1.666		Bulk Density	227.6 gr./in. ³ 0.900 gm/cm ³

Calculated and Estimated Data:

Bullet Shank Seating Depth	0.479 in.	12.17 mm	Capacity Displaced by Seated Bullet	0.0249 in. ³	0.408 cm ³
Useable Case Capacity	0.1902 in. ³	3.118 cm ³	Bullet Travel at Muzzle Exit	22.82 in.	579.61 mm
Loading Ratio("Density") / Filling	90.1 %		Charge Fraction Burnt at Shot Start	1.84 %	

Predicted Data:

Maximum Chamber Pressure	48530 psi.	3346 bar	Bullet Travel at Pmax	1.94 in.	49.3 mm
at Muzzle Exit:					
Bullet Velocity	3204 fps.	976.5 m/s	Pressure at Muzzle	7946 psi.	548 bar
Bullet Energy	1823 ft.lbs.	2472 Joule	Bullet Barrel Time	1.104 ms	
Propellant Burnt	99.9 %		Ballistic Efficiency	26.4 %	

Check Loading Manuals for Safe Minimum Charge Weight to Avoid Hazardous Ignition Conditions like Secondary Explosion Effects !
 Real maximum (peak) of pressure is reached while bullet moves within barrel.
 End of combustion occurs after the bullet's base passes muzzle.

