

**QuickLOAD® V.3.6 © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany**

WARNING: Since we have no control over equipment or data which may be used with this program, no responsibility is implied or assumed for results obtained through its use. Input data and results may be incorrect or wrong. Therefore the use of this data for loading ammunition can cause serious injury to personnel and material. The computer-results had to be checked against data available in current loading manuals.

**LOT-TO-LOT VARIATIONS OF POWDERS, PRIMER SUBSTITUTION AND COMPONENT CHANGE OFTEN RAISE PRESSURES TO UNSAFE LEVELS. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS DATA FOR LOADING PURPOSES.**

QuickLOAD® V.3.6.02 #130542, © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

<b>User Data:</b>	<b>Date:8-Apr-2015</b>	<b>Time:22:32:43</b>	<b>File: xpert 25-06 rem 80gr.dat</b>	
<b>Cartridge / Caliber</b>	<b>.25-06 Rem.</b>	<b>Bullet</b>	<b>.257, 80, XPERT</b>	
Maximum Average Pressure, allowed	65267 psi.	4500 bar (Piezo CIP)	with flatbase	
Groove Caliber	0.257 in.	6.53 mm	Bullet Weight	80.0 gr. 5.18 gm
Case Capacity, overflow	65.8 gr. H2O	4.272 cm <sup>3</sup>	Bullet Length	1.063 in. 27.0 mm
Case Length	2.489 in.	63.22 mm	Bullet Seating Depth	0.481 in. 12.22 mm
Cartridge O.A. Length	3.071 in.	78.0 mm	Barrel/Tube Length	24.0 in. 609.6 mm
Shot Start / Init Pressure	3625 psi.	249.94 bar	Cross Section Area of Bore	0.05118 in. <sup>2</sup> 0.3302 cm <sup>2</sup>
<b>Propellant type</b>	<b>Somchem S365</b>			
Charge Weight	54.0 gr.	3.499 gm	Load Density	229.1 gr./in. <sup>3</sup> 0.906 gm/cm <sup>3</sup>
Heat of Explosion, Potential	238.8 J/gr.	3685 J/gm	Energy Density of Charge	54716 J/in. <sup>3</sup> 3339 J/cm <sup>3</sup>
Propellant Solid Density	404.63 gr./in. <sup>3</sup>	1.6 gm/cm <sup>3</sup>	Used Ratio of Specific Heats cp/cv	1.239
Burning Rate Factor Ba	0.44 1/s		Weighting Factor	0.55
Burning Function Limit Z1	0.605		Prog.-/ Degressivity Factor a0	1.715
Factor b	2.271		Bulk Density	231.4 gr./in. <sup>3</sup> 0.915 gm/cm <sup>3</sup>

**Calculated and Estimated Data:**

Bullet Shank Seating Depth	0.481 in.	12.22 mm	Capacity Displaced by Seated Bullet	0.025 in. <sup>3</sup>	0.41 cm <sup>3</sup>
Useable Case Capacity	0.2357 in. <sup>3</sup>	3.862 cm <sup>3</sup>	Bullet Travel at Muzzle Exit	21.99 in.	558.6 mm
Loading Ratio("Density") / Filling	99.0 %		Charge Fraction Burnt at Shot Start	1.36 %	

**Predicted Data:**

Maximum Chamber Pressure	51069 psi.	3521 bar	Bullet Travel at Pmax	3.21 in.	81.5 mm
<b>at Muzzle Exit:</b>					
Bullet Velocity	3466 fps.	1056.5 m/s	Pressure at Muzzle	11209 psi.	773 bar
Bullet Energy	2134 ft.lbs.	2894 Joule	Bullet Barrel Time	1.074 ms	
Propellant Burnt	99.9 %		Ballistic Efficiency	22.4 %	

Check Loading Manuals for Safe Minimum Charge Weight to Avoid Hazardous Ignition Conditions like Secondary Explosion Effects !  
 Real maximum (peak) of pressure is reached while bullet moves within barrel.  
 End of combustion occurs after the bullet's base passes muzzle.

