

QuickLOAD® V.3.6 © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

WARNING: Since we have no control over equipment or data which may be used with this program, no responsibility is implied or assumed for results obtained through its use. Input data and results may be incorrect or wrong. Therefore the use of this data for loading ammunition can cause serious injury to personnel and material. The computer-results had to be checked against data available in current loading manuals.

LOT-TO-LOT VARIATIONS OF POWDERS, PRIMER SUBSTITUTION AND COMPONENT CHANGE OFTEN RAISE PRESSURES TO UNSAFE LEVELS. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS DATA FOR LOADING PURPOSES.

QuickLOAD® V.3.6.02 #130542, © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

User Data:	Date:9-Apr-2015	Time:17:48:35	File: xpert 3006 spring 130gr.dat	
Cartridge / Caliber	.30-06 Spring. (CIP)	Bullet	.308, 130GR XPERT TARGET	
Maximum Average Pressure, allowed	58740 psi.	4050 bar (Piezo CIP)	with flatbase	
Groove Caliber	0.308 in.	7.82 mm	Bullet Weight	130.0 gr. 8.42 gm
Case Capacity, overflow	68.2 gr. H2O	4.428 cm ³	Bullet Length	1.236 in. 31.4 mm
Case Length	2.494 in.	63.35 mm	Bullet Seating Depth	0.541 in. 13.75 mm
Cartridge O.A. Length	3.189 in.	81.0 mm	Barrel/Tube Length	24.0 in. 609.6 mm
Shot Start / Init Pressure	3625 psi.	249.94 bar	Cross Section Area of Bore	0.07366 in. ² 0.4752 cm ²
Propellant type	Somchem S335			
Charge Weight	47.0 gr.	3.046 gm	Load Density	204.6 gr./in. ³ 0.809 gm/cm ³
Heat of Explosion, Potential	240.4 J/gr.	3710 J/gm	Energy Density of Charge	49178 J/in. ³ 3001 J/cm ³
Propellant Solid Density	407.15 gr./in. ³	1.61 gm/cm ³	Used Ratio of Specific Heats cp/cv	1.224
Burning Rate Factor Ba	0.624 1/s		Weighting Factor	0.55
Burning Function Limit Z1	0.35		Prog.-/ Degressivity Factor a0	2.299
Factor b	1.666		Bulk Density	227.6 gr./in. ³ 0.900 gm/cm ³

Calculated and Estimated Data:

Bullet Shank Seating Depth	0.541 in.	13.75 mm	Capacity Displaced by Seated Bullet	0.0404 in. ³	0.662 cm ³
Useable Case Capacity	0.2298 in. ³	3.766 cm ³	Bullet Travel at Muzzle Exit	22.05 in.	560.0 mm
Loading Ratio("Density") / Filling	89.9 %		Charge Fraction Burnt at Shot Start	1.85 %	

Predicted Data:

Maximum Chamber Pressure	44673 psi.	3080 bar	Bullet Travel at Pmax	1.69 in.	43.0 mm
at Muzzle Exit:					
Bullet Velocity	2835 fps.	864.0 m/s	Pressure at Muzzle	7115 psi.	491 bar
Bullet Energy	2319 ft.lbs.	3145 Joule	Bullet Barrel Time	1.183 ms	
Propellant Burnt	99.5 %		Ballistic Efficiency	27.8 %	

Check Loading Manuals for Safe Minimum Charge Weight to Avoid Hazardous Ignition Conditions like Secondary Explosion Effects !
 Real maximum (peak) of pressure is reached while bullet moves within barrel.
 End of combustion occurs after the bullet's base passes muzzle.

