

QuickLOAD® V.3.6 © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

WARNING: Since we have no control over equipment or data which may be used with this program, no responsibility is implied or assumed for results obtained through its use. Input data and results may be incorrect or wrong. Therefore the use of this data for loading ammunition can cause serious injury to personnel and material. The computer-results had to be checked against data available in current loading manuals.

LOT-TO-LOT VARIATIONS OF POWDERS, PRIMER SUBSTITUTION AND COMPONENT CHANGE OFTEN RAISE PRESSURES TO UNSAFE LEVELS. THE USER MUST ASSUME THE ENTIRE RISK OF USING THIS DATA FOR LOADING PURPOSES.

QuickLOAD® V.3.6.02 #130542, © Copyright 1987-2010 - H.Broemel, Babenhausen, Germany

User Data:	Date:8-Apr-2015	Time:22:20:46	File: xpert 6mm rem 68 gr.dat	
Cartridge / Caliber	6 mm Rem.	Bullet	.243, 68, XPERT Bullet	
Maximum Average Pressure, allowed	62366 psi.	4300 bar (Piezo CIP)	with flatbase	
Groove Caliber	0.243 in.	6.17 mm	Bullet Weight	68.0 gr. 4.41 gm
Case Capacity, overflow	54.4 gr. H2O	3.532 cm ³	Bullet Length	1.031 in. 26.19 mm
Case Length	2.223 in.	56.46 mm	Bullet Seating Depth	0.437 in. 11.1 mm
Cartridge O.A. Length	2.817 in.	71.55 mm	Barrel/Tube Length	24.0 in. 609.6 mm
Shot Start / Init Pressure	3625 psi.	249.94 bar	Cross Section Area of Bore	0.04576 in. ² 0.2952 cm ²
Propellant type	Somchem S365			
Charge Weight	46.0 gr.	2.981 gm	Load Density	235.7 gr./in. ³ 0.932 gm/cm ³
Heat of Explosion, Potential	238.8 J/gr.	3685 J/gm	Energy Density of Charge	56273 J/in. ³ 3434 J/cm ³
Propellant Solid Density	404.63 gr./in. ³	1.6 gm/cm ³	Used Ratio of Specific Heats cp/cv	1.239
Burning Rate Factor Ba	0.44 1/s		Weighting Factor	0.5
Burning Function Limit Z1	0.605		Prog.-/ Degressivity Factor a0	1.715
Factor b	2.271		Bulk Density	231.4 gr./in. ³ 0.915 gm/cm ³

Calculated and Estimated Data:

Bullet Shank Seating Depth	0.437 in.	11.1 mm	Capacity Displaced by Seated Bullet	0.0203 in. ³	0.333 cm ³
Useable Case Capacity	0.1952 in. ³	3.199 cm ³	Bullet Travel at Muzzle Exit	22.21 in.	564.24 mm
Loading Ratio("Density") / Filling	101.8 % = compressed		Charge Fraction Burnt at Shot Start	1.27 %	

Predicted Data:

Maximum Chamber Pressure	47044 psi.	3244 bar	Bullet Travel at Pmax	2.73 in.	69.5 mm
at Muzzle Exit:					
Bullet Velocity	3480 fps.	1060.8 m/s	Pressure at Muzzle	10878 psi.	750 bar
Bullet Energy	1829 ft.lbs.	2479 Joule	Bullet Barrel Time	1.070 ms	
Propellant Burnt	98.9 %		Ballistic Efficiency	22.6 %	

Check Loading Manuals for Safe Minimum Charge Weight to Avoid Hazardous Ignition Conditions like Secondary Explosion Effects !
 Real maximum (peak) of pressure is reached while bullet moves within barrel.
 End of combustion occurs after the bullet's base passes muzzle.

